SNU 5 Plus (GB) SMALL WATER HEATER

Experience high quality in a compact design

DHW heating at its best: this small water heater for undersink installation has an attractive design that will blend perfectly into your room. As the most compact in their class, the smaller models in particular take up very little space. Despite the small dimensions of this small water heater, it is certainly not lacking in output.

Convenient temperature adjustment

You get hot water quickly, without having to wait. Vary the temperature with the high quality haptic rotary selector. The small water heater requires little energy to keep the water constantly warm for you at the temperature you have selected. Another advantage: replacing an older model is very easy, as you can use the same wall mounting bracket for this small water heater.

The main features

Compact and high quality small water heater for undersink installation

Hot water available immediately

Safe use due to adjustable mechanical temperature limit as anti-scalding protection

Low energy losses at the tap thanks to integral thermostop function

Quick and easy replacement of older appliances thanks to universal wall mounting bracket

Optimised DHW heating for higher efficiency with ECO mode

No dripping during heat-up, reduced scaling plus water savings thanks to the anti-drip function

PRODUCT-NO.: 204971





SNU 10 Plus (GB) Product-No.: 204981



Technical data

| Connected load | 2 kW | 2 kW |
|--|--------------------|-------------------|
| Rated output 2 | 2,0 kW | 2,0 kW |
| Power supply | 1/N/PE | 1/N/PE |
| Rated voltage | 230 V | 230 V |
| Fuse protection 2 | 10 A | 10 A |
| Frequency | 50-60 Hz | 50-60 Hz |
| Energy efficiency class | А | А |
| Standby energy consumption/24 h at 65 °C | 0.19 kWh | 0.31 kWh |
| Standby energy consumption/24 h at 38 °C | 0.07 kWh | 0.11 kWh |
| Nominal capacity | 5 | 10 l |
| Mixed water amount at 40 °C | 9,3 l | 19 l |
| Temperature setting range | 35-85 °C | 35-85 °C |
| Version | Small water heater | Small water heate |
| Туре | non-pressurised | non-pressurised |
| Installation type | Undersink | Undersink |
| With tap | - | - |
| Colour | white | white |
| Cable length | 0,9 m | 0,9 m |
| Operation | manual | manual |
| Temperature limit | • | • |
| IP rating | IP24 D | IP24 D |

| Height | 423 mm | 506 mm |
|--------|---------|---------|
| Width | 240 mm | 290 mm |
| Depth | 212 mm | 282 mm |
| Weight | 2.90 kg | 4.20 kg |

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help: Call 0151 436 96 Or send an e-mail to sales@stiebel-eltron.ie

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.