# CNS 250 Connect UK

PRODUCT-NO.: 205644

Use an intuitive app to control your home heating and gain full transparency of energy consumption and costs through user-friendly statistics. Whether you just don't want to get up off the sofa or you are flying home from accross the world, you can login to the app to set your heating just how you want it.



The main features

Suitable for up to 10 rooms with up to 4 heaters each

Individual time programmes for each room with 2 or more heaters

Option to use external room temperature sensors for even more comfort in larger rooms where 2 or more units are installed

Installation wizard for initial setup

Metal casing and slimline design

Weekly timer, frost protection and open window detection for maximum operating efficiencies

Unit learns when to turn on to have your room at your target temperatures right at the start of your programmed times





Туре	CNS 50 Connect UK	CNS 75 Connect UK	CNS 100 Connect UK
Part no.	205639	205640	205641
Wärmeleistung			
Rated heating output Pnom	0.50 kW	0.75 kW	1.00 kW
Minimum heating output (standard value) Pmin	0.00 kW	0.00 kW	0.00 kW
Maximum continuous heating output Pmax,c	0.50 kW	0.75 kW	1.00 kW
Hilfsstromverbrauch			
Auxiliary power consumption with rated heating output elmax	0.00 kW	0.00 kW	0.00 kW
Auxiliary power consumption with minimum heating output elmin	0.00 kW	0.00 kW	0.00 kW
Auxiliary power consumption in standby mode elSB	0.00 kW	0.00 kW	0.00 kW
Art der Wärmeleistung/Raumtemperaturkontrol	le		
Type of heating output/room temperature control: Single stage heating output, no room temperature control	-	-	-
Type of heating output/room temperature control: Two or more manually adjustable stages, no room temperature control	-	-	-
Type of heating output/room temperature control: With mechanic thermostat room temperature control	-	-	-
Type of heating output/room temperature control: With electronic room temperature control	-	-	-
Type of heating output/room temperature control: Electronic room temperature control plus day timer	-	-	-
Type of heating output/room temperature control: Electronic room temperature control plus week timer	X	X	X
Sonstige Regelungsoptionen			
Other control options: Room temperature control, with presence detection	-	-	-
Other control options: Room temperature control, with open window detection	Х	x	х
Other control options: With remote control option	Х	x	x
Other control options: With adaptive control of heating startup	х	x	x
Other control options: With operating time limitation	-	-	-
Other control options: With black bulb sensor	-	-	-



## Product datasheet: product information according to EU Regulation 1188/2015



Туре	CNS 150 Connect UK	CNS 200 Connect UK	CNS 250 Connect UK
Part no.	205642	205643	205644
Wärmeleistung			
Rated heating output Pnom	1.50 kW	2.00 kW	2.50 kW
Minimum heating output (standard value) Pmin	0.00 kW	0.00 kW	0.00 kW
Maximum continuous heating output Pmax,c	1.50 kW	2.00 kW	2.50 kW
Hilfsstromverbrauch			
Auxiliary power consumption with rated heating output elmax	0.00 kW	0.00 kW	0.00 kW
Auxiliary power consumption with minimum heating output elmin	0.00 kW	0.00 kW	0.00 kW
Auxiliary power consumption in standby mode eISB	0.00 kW	0.00 kW	0.00 kW

## Art der Wärmeleistung/Raumtemperaturkontrolle

Type of heating output/room temperature control: Single stage heating output, no room temperature control	-	-	-
Type of heating output/room temperature control: Two or more manually adjustable stages, no room temperature control	-	-	-
Type of heating output/room temperature control: With mechanic thermostat room temperature control	-	-	-
Type of heating output/room temperature control: With electronic room temperature control	-	-	-
Type of heating output/room temperature control: Electronic room temperature control plus day timer	-	-	-
Type of heating output/room temperature control: Electronic room temperature control plus week timer	x	Х	х

## Sonstige Regelungsoptionen

Other control options: Room temperature control, with presence detection	-	-	-
Other control options: Room temperature control, with open window detection	X	х	x
Other control options: With remote control option	х	x	х
Other control options: With adaptive control of heating startup	х	x	х
Other control options: With operating time limitation	-	-	-
Other control options: With black bulb sensor	-	-	-



							=
=							

Туре	CNS 300 Connect UK
Part no.	205645
Wärmeleistung	
Rated heating output Pnom	3.00 kW
Minimum heating output (standard value) Pmin	0.00 kW
Maximum continuous heating output Pmax,c	3.00 kW
Maximum continuous nearing output i max,c	5.00 KW
Hilfsstromverbrauch	5.00 KV
	0.00 kW
Hilfsstromverbrauch	

### Art der Wärmeleistung/Raumtemperaturkontrolle

- · ·	
Type of heating output/room temperature control: Single stage heating output, no room temperature control	-
Type of heating output/room temperature control: Two or more manually adjustable stages, no room temperature control	-
Type of heating output/room temperature control: With mechanic thermostat room temperature control	-
Type of heating output/room temperature control: With electronic room temperature control	-
Type of heating output/room temperature control: Electronic room temperature control plus day timer	-
Type of heating output/room temperature control: Electronic room temperature control plus week timer	x
Sonstige Regelungsoptionen	
Other control options: Room temperature control, with presence detection	-
Other control options: Room temperature control, with open window detection	x
Other control options: With remote control option	х
Other control options: With adaptive control of heating startup	x
Other control options: With operating time limitation	-
Other control options: With black bulb sensor	-



Depth including wall mounting bracket



#### **Contact information**

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help: Call 0151 436 96 Or send an e-mail to sales@stiebel-eltron.ie

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.